

## **Hand Tools Multimeters**

## Fluke 179 True-RMS Digital Multimeter

The Fluke 179 True-rms Digital Multimeter is the industry-standard troubleshooting tool for electrical and electronic systems. This incredibly versatile multimeter makes a perfect front-line troubleshooting tool with an input protection rating of CAT III 1000 V, CAT IV 600 V. The built-in temperature measurement with the included thermocouple, analog bar graph and backlit digital display make it easier to take the measurements you need.



## 1. Fluke 179 True-RMS Digital Multimeter



## Key Features

- 1000V AC/DC; 10A AC/DC (with test leads and current jacks); resistance to 50 M $\Omega$ ; capacitance to 10,000  $\mu$ F, frequency to 100 kHz; temperature from -40 °C to 400 °C
- Robust, fast and accurate with manual and automatic ranging, Display Hold, Auto Hold, and Min/Max-Average recording
- Backlit digital display, analog bar graph, and built-in temperature measurements with included thermocouple

Specifications		
Voltage DC	Accuracy <sup>1</sup>	±(0.09% + 2)
	Max. resolution	0.1 mV
	Maximum	1000 V
Voltage AC	Accuracy <sup>1</sup>	±(1.0% + 3)
	Max. resolution	0.1 mV
	Maximum	1000 V
Current DC	Accuracy <sup>1</sup>	±(1.0% + 3)
	Max. resolution	0.01 mA
	Maximum	10 A
Current AC	Accuracy <sup>1</sup>	±(1.5% + 3)



	ı I	
	Max. resolution	0.01 mA
	Maximum	10 A
Resistance	Accuracy <sup>1</sup>	±(0.9% + 1)
	Max. resolution	0.1 Ω
	Maximum	50 ΜΩ
Capacitance	Accuracy <sup>1</sup>	±(1.2% + 2)
	Max. resolution	1 nF
	Maximum	10,000 μF
Frequency	Accuracy <sup>1</sup>	±(0.1% + 1)
	Max. resolution	0.01 Hz
	Maximum	100 kHz
Temperature	Accuracy <sup>1</sup>	±(1.0% + 10)
	Max. resolution	0.1°C
	Range	-40°C / 400°C
1. Accuracies are best accuracies for each function		
Environmental Specifications		
Operating temperature	-10°C to +50°C	
Storage temperature	-30°C to +60°C	
Humidity (without condensation)	0% – 90% (0°C – 35°C) 0% – 70% (35°C – 50°C)	
Safety Specifications		
Overvoltage category	EN 61010–1 to 1000 V CA EN 61010–1 to 600 V CAT	



Agency approvals	UL, CSA, TÜV listed and VDE Pending	
Mechanical and General Specifications		
Size	43 x 90 x 185 mm	
Weight	420 g	
Warranty	Lifetime	
Battery life	Alkaline ~200 hours typical, without backlight	