

CLAMPMETER

➤ **Fluke 325 True RMS Clamp Meter**

The Fluke 325 True-rms Clamp Meter is a reliable, versatile troubleshooting tool for commercial and residential electricians. Featuring a slim design for easy transport and use, and a large display for efficient troubleshooting.

1. Fluke 325 True RMS Clamp Meter



Key Features

- True-rms AC/DC current, voltage, temperature, frequency
- Clamp meter, test leads, K-type thermocouple and soft case
- Versatile tool performs most front-line measurement tasks

Specifications

AC current	Range	40.00 A / 400.0 A
	Accuracy	2% $\pm$ 5 digits (45 Hz to 65 Hz) 2.5% $\pm$ 5 digits (65 Hz to 400 Hz)
DC current	Range	40.00 A / 400.0 A
	Accuracy	2% $\pm$ 5 digits
AC voltage	Range	600.0 V
	Accuracy	1.5% $\pm$ 5 digits
DC voltage	Range	600.0 V
	Accuracy	1.0% $\pm$ 5 digits
Resistance	Range	400.0 Ω / 4000 Ω / 40.00 k Ω

	Accuracy	1.0% ± 5 digits
Continuity		≤ 30 Ω
Capacitance		0 to 100.0 μF / 100μF to 1000 μF
Frequency		5.0 Hz to 500.0 Hz
AC response		True-RMS
Backlight		Yes
Data hold		Yes
Contact temperature		-10.0°C to 400.0°C (14.0°F to 752.0°F)
Min/Max		Yes
Size	H x W x D (mm)	207 x 75 x 34
	Max wire diameter	30 mm (600 MCM)
	Weight	283 g
Category rating		CAT III 600 V CAT IV 300 V
Warranty		Two-year